


Spot · BS SERIES Red 620nm

lumher



24 V
DC

NOT
CASCADABLE

IP65

M12A

MACHINE VISION

POWER 1x
STROBE 3x

INTEGRATED
CONTROLLER

36
MONTHS

EU
MADE IN SPAIN

Technical specifications

Power supply voltage	24 Vdc ±5%	
Trigger input	24 Vdc PNP	
Max. on time	Power = unlimited	Strobe = 50 ms
Max. working cycle	Power = 1	Strobe = 1/4
Max. number of cascable modules	This luminaire is not cascable	
Wavelength	Red	620 nm
Beam angle	Transparent	6° 15° 40°
Electrical protections	Transient overvoltages Polarity reversal Current sabitizer	YES YES YES
IP Rating	IP65	
Protection type	Class III	
Operating temperature	-10 a +40 °C	
Body material	Anodized aluminum	
Lenses material	PMMA plastic	
Connection types	M12A connector	
Standards	RoHs, CE	

Connection

M12A input	Power	Master Power - Strobe
Pin 1 - Brown	+24 Vdc	+24 Vdc
Pin 2 - White	Not connected	Trigger NPN
Pin 3 - Blue	0 Vdc	0 Vdc
Pin 4 - Black	Not connected	Trigger PNP


M12A Male



Fixings

B00S1



BS · 620nm




lumher

Measures

BS 1



Selection guide





Measures in mm

BS · 620nm

lumher

Model BS · Red 620 nm



620nm

RED

→

TRANSPARENT
6°

→

TRANSPARENT
15°

→

TRANSPARENT
30°

PHOTOBIOLOGICAL
RISK

RG1 - LOW

60.000h

LIFESPAN

Table of characteristics

BS 1 ...	Width	Length	Weight	Luminous flux ⁽¹⁾		Power consumed	
	(mm)	(mm)	(g)	(lm)		(W)	
				POWER	STROBE	POWER	STROBE
BS 1 ...	125	125	500	320	950	9,4	41,3

(1) The luminous flux (lm) is before the lenses.